

Sprinkler Cabinets

3, 6, & 12 Sprinklers, 1/2 or 3/4 Inch NPT

6 ESFR Sprinklers, 3/4 or 1 Inch NPT

General Description

Tyco® Sprinkler Cabinets are constructed of metal enclosures with hinged covers designed to provide on-site storage of an emergency supply of sprinklers and a sprinkler wrench.

NFPA 13 requires a representative number of each type of sprinkler used in a sprinkler system to be stored in a cabinet on-site to allow for immediate removal and replacement of sprinklers that may have operated or become damaged.

Sprinkler Cabinets are manufactured of heavy gauge steel with knock-outs to accommodate NPT threaded sprinklers and are painted an attractive red enamel.

WARNINGS

The Sprinkler Cabinets described herein must be installed and maintained in compliance with this document, as well as with the applicable standards of the National Fire Protection Association, in addition to the standards of any other authorities having jurisdiction. Failure to do so may impair the performance of these devices.

The owner is responsible for maintaining their fire protection system and devices in proper operating condition. The installing contractor or sprinkler manufacturer should be contacted with any questions.




Technical Data

Material
Carbon Steel

Weights

3 Sprinkler Cabinet	1.5 Lbs. (0,68 kg)
6 Sprinkler Cabinet	2.3 Lbs. (1,04 kg)
12 Sprinkler Cabinet	4.0 Lbs. (1,81 kg)
6 ESFR Sprinkler Cabinet	3.3 Lbs. (1,36 kg)






FIGURE 1
3 SPRINKLER CABINET




FIGURE 2
6 SPRINKLER CABINET




FIGURE 3
12 SPRINKLER CABINET




FIGURE 4
6 ESFR SPRINKLER CABINET

Installation

Sprinkler Cabinets are designed with two 3/16 Inch (4,7 mm) diameter holes for wall mounting or direct attachment to the system riser with a strap-type hanger. The Sprinkler Cabinet should be installed at or near the system control valve and must be stocked with an adequate supply of spare sprinklers and a sprinkler wrench.

The stock of spare sprinklers should include sprinklers of each type and temperature rating as are installed in the sprinkler system, in the following quantities:

Sprinklers In System	Spare Sprinklers Required
Under 300	6
300-1000	12
Over 1000	24

The 3, 6, and 12 Sprinkler Cabinets are designed to accept both 1/2 & 3/4 Inch NPT threaded sprinklers, whereas the 6 ESFR Sprinkler Cabinets are designed to accept both 3/4 & 1 Inch NPT threaded sprinklers. As necessary, insert a screwdriver blade from the front top of the shelf and under the near bottom part of the knockout annular ring. Press the screwdriver handle down to remove the knockout ring.

Care and Maintenance

The Sprinkler Cabinet, wrench, and stock of spare sprinklers should be inspected at least quarterly. The following items should be checked:

- The Sprinkler Cabinet should be readily accessible, and not exposed to a corrosive atmosphere or temperatures in excess of 100°F (38°C).
- The stock of spare sprinklers should include an adequate number of each type and temperature rating.
- The stock of sprinklers must be in good condition.
- A sprinkler wrench of the appropriate type must be included in the Sprinkler Cabinet.

Limited Warranty

Products manufactured by Tyco Fire & Building Products (TFBP) are warranted solely to the original Buyer for ten (10) years against defects in material and workmanship when paid for and properly installed and maintained under normal use and service. This warranty will expire ten (10) years from date of shipment by TFBP. No warranty is given for products or components manufactured by companies not affiliated by ownership with TFBP or for products and components which have been subject to misuse, improper installation, corrosion, or which have not been installed, maintained, modified or repaired in accordance with applicable Standards of the National Fire Protection Association, and/or the standards of any other Authorities Having Jurisdiction. Materials found by TFBP to be defective shall be either repaired or replaced, at TFBP's sole option. TFBP neither assumes, nor authorizes any person to assume for it, any other obligation in connection with the sale of products or parts of products. TFBP shall not be responsible for sprinkler system design errors or inaccurate or incomplete information supplied by Buyer or Buyer's representatives.

In no event shall TFBP be liable, in contract, tort, strict liability or under any other legal theory, for incidental, indirect, special or consequential damages, including but not limited to labor charges, regardless of whether TFBP was informed about the possibility of such damages, and in no event shall TFBP's liability exceed an amount equal to the sales price.

The foregoing warranty is made in lieu of any and all other warranties, express or implied, including warranties of merchantability and fitness for a particular purpose.

This limited warranty sets forth the exclusive remedy for claims based on failure of or defect in products, materials or components, whether the claim is made in contract, tort, strict liability or any other legal theory.

This warranty will apply to the full extent permitted by law. The invalidity, in whole or part, of any portion of this warranty will not affect the remainder.

Ordering Procedure

When placing an order, indicate the full product name. Contact your local distributor for availability.

- Sprinkler Cabinet:**
Specify: (Description), P/N (specify).
- 3 Sprinkler Cabinet. P/N 1177
 - 6 Sprinkler Cabinet. P/N 1119
 - 12 Sprinkler Cabinet. P/N 1124
 - 6 ESFR Sprinkler Cabinet P/N 1111